

## MULTIMAX MP 522 - Especificações técnicas



### Description

MULTIMAX MP 522 é o pneu polivalente da BKT desenvolvido para ser utilizado em muitos campos no setor agroindustrial. É apropriado para todas as operações de elevação e carga em veículos tais como levantadores telescópicos e pás compactas. Estabilidade e tração são os pontos de força associados à resistência excepcional aos furos. Graças ao composto de borracha especial, MULTIMAX MP 522 fornece uma resistência extraordinária aos cortes e lacerações.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Carregadora compacta • Levantador telescópico

Industrial: Carregadora compacta • Levantador telescópico

Version	STANDARD
Type	TL
Tyre Size	460/70 R 24 IND (17.5L R 24)
LI/SS	159 A8/B

## Dimensions International Standard

Section Width (mm)	465
Overall Diameter (mm)	1250
Static Loaded Radius (mm)	568
Rolling Circumference (mm)	3766
SRI (mm)	600
Rim Rec	DW 15 L
Rim Alt	DW 14 L ; DW 16 L
ECE	E4-106R-002396

## Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	2100	2495	2845	3240	3635	3895	4375	-	-
40	2100	2495	2845	3240	3635	3895	4375	-	-
30	2250	2675	3050	3470	3890	4170	4685	-	-
25	2335	2775	3160	3600	4035	4330	4860	-	-
10 Cyc	2565	3155	3710	4270	4860	5285	5975	6305	6565
Static	3930	4835	5690	6545	7450	8105	9160	9665	10065

Printed on 25/04/2024 23:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..