

## MULTIMAX MP 522 - Especificações técnicas



### Description

MULTIMAX MP 522 é o pneu polivalente da BKT desenvolvido para ser utilizado em muitos campos no setor agroindustrial. É apropriado para todas as operações de elevação e carga em veículos tais como levantadores telescópicos e pás compactas. Estabilidade e tração são os pontos de força associados à resistência excepcional aos furos. Graças ao composto de borracha especial, MULTIMAX MP 522 fornece uma resistência extraordinária aos cortes e lacerações.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Carregadora compacta • Levantador telescópico

Industrial: Carregadora compacta • Levantador telescópico

|           |                 |
|-----------|-----------------|
| Version   | STANDARD        |
| Type      | TL              |
| Tyre Size | 540/70 R 24 IND |
| LI/SS     | 168 A8/B        |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94052264        |
| Section Width (inch)         | 20.9            |
| Overall Diameter (inch)      | 53.8            |
| Static Loaded Radius (inch)  | 24.1            |
| Rolling Circumference (inch) | 162.7           |
| Rim Rec                      | DW 16 L         |
| Rim Alt                      | DW 18 L         |
| ECE                          | E11-106R-002967 |

## Load capacity (lbs)

| mph / psi | 23    | 29    | 35    | 41    | 46    | 51    | 58    | 61    | 64    |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 5930  | 7040  | 8020  | 9140  | 10250 | 10990 | 12350 | -     | -     |
| 25        | 5930  | 7040  | 8020  | 9140  | 10250 | 10990 | 12350 | -     | -     |
| 20        | 6350  | 7540  | 8600  | 9790  | 10980 | 11770 | 13220 | -     | -     |
| 15        | 6590  | 7830  | 8920  | 10150 | 11390 | 12210 | 13710 | -     | -     |
| 5 Cyc.    | 7230  | 8900  | 10470 | 12040 | 13710 | 14910 | 16850 | 17780 | 18520 |
| Static    | 11080 | 13630 | 16050 | 18460 | 21020 | 22860 | 25850 | 27260 | 28390 |

Printed on 18/04/2024 12:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..