

MULTIMAX MP 525 - Especificações técnicas



Description

O MULTIMAX MP 525 é um pneu radial multifunções integralmente em aço concebido para manipuladores telescópicos, pás carregadoras compactas e motoniveladoras para aplicações agroindustriais. O pneu foi especialmente desenvolvido para transportar cargas pesadas a velocidades mais elevadas, dentro e fora da estrada. Com efeito, o design do piso não direcional e de grandes dimensões proporciona uma tração excecional em qualquer superfície, para além de excelentes propriedades de autolimpeza. A parede lateral forte garante uma estabilidade lateral excecional no modo de elevação, tornando-o a escolha ideal para operações agrícolas e de manuseamento de materiais. O MULTIMAX MP 525 é feito de um composto de piso único, resistente a cortes e "chips", que se traduz numa vida útil mais duradoura graças à sua extraordinária resistência contra qualquer tipo de cortes e furos.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Carregadora compacta • Motoniveladora •
Levantador telescópico

Version	STANDARD
Type	TL
Tyre Size	405/70 R 18 (15.5/70 R 18)
LI/SS	146 J/141 B/153 A2

Dimensions International Standard

Overall Width (mm)	405
Overall Diameter (mm)	1025
Static Loaded Radius (mm)	462
Rolling Circumference (mm)	3122
Rim Rec	13
Rim Alt	11; 12
ECE	E11-54R-0022030

Load capacity (Kg)

km/h / bar	3.75	4.00
100	2800	3000
50	2575	-
10	3650	-

Printed on 29/04/2024 20:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..