

MULTIMAX MP 529 - Especificações técnicas



Description

O MULTIMAX MP 529 é um pneu radial multiusos com cintas de aço, concebido para empilhadores telescópicos em aplicações industriais. O desenho do piso foi especialmente desenvolvido para superfícies duras, e a parede lateral robusta e a grande área de contacto garantem uma estabilidade excecional no modo de elevação. O MULTIMAX MP 529 inclui ainda uma forte carcaça resistente a perfurações, e é fabricado com um composto especial resistente a cortes e raspagens, garantindo assim uma durabilidade extraordinária e uma longa vida útil.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Levantador telescópico

Version	STANDARD
Type	TL
Tyre Size	340/80 R 18
LI/SS	143 A8/B

Dimensions International Standard

Section Width (mm)	343
Overall Diameter (mm)	1001
Static Loaded Radius (mm)	445
Rolling Circumference (mm)	3007
SRI (mm)	475
Rim Rec	11 ; 11 SDC ; W 11
Rim Alt	W 10 ; 12 ; 12 SDC
ECE	E11-106R-002972

Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1310	1555	1775	2020	2265	2430	2725	-	-
40	1310	1555	1775	2020	2265	2430	2725	-	-
30	1405	1665	1900	2165	2425	2600	2920	-	-
25	1455	1725	1970	2240	2515	2695	3025	-	-
10 Cyc.	1600	1965	2315	2660	3030	3295	3725	3930	4090
Static	2450	3010	3545	4080	4640	5050	5710	6020	6270

Printed on 27/04/2024 08:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..