

MULTIMAX MP 529 - Especificações técnicas



Description

O MULTIMAX MP 529 é um pneu radial multiusos com cintas de aço, concebido para empilhadores telescópicos em aplicações industriais. O desenho do piso foi especialmente desenvolvido para superfícies duras, e a parede lateral robusta e a grande área de contacto garantem uma estabilidade excecional no modo de elevação. O MULTIMAX MP 529 inclui ainda uma forte carcaça resistente a perfurações, e é fabricado com um composto especial resistente a cortes e raspagens, garantindo assim uma durabilidade extraordinária e uma longa vida útil.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Levantador telescópico

Version	STANDARD
Type	TL
Tyre Size	340/80 R 18
LI/SS	143 A8/B

Dimensions US Standard

Usa code	94054305
Section Width (inch)	13.5
Overall Diameter (inch)	39.4
Static Loaded Radius (inch)	17.5
Rolling Circumference (inch)	118.4
Rim Rec	11 ; 11 SDC ; W 11
Rim Alt	W 10 ; 12 ; 12 SDC
ECE	E11-106R-002972

Load capacity (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	2890	3430	3910	4450	4990	5360	6010	-	-
25	2890	3430	3910	4450	4990	5360	6010	-	-
20	3100	3670	4190	4770	5350	5730	6440	-	-
15	3210	3800	4340	4940	5540	5940	6670	-	-
5 Cvc.	3530	4330	5100	5860	6680	7260	8210	8660	9020
Static	5400	6640	7810	8990	10230	11130	12590	13270	13820

Printed on 27/04/2024 09:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..