

MULTIMAX MP 538 - Especificações técnicas



Description

O MULTIMAX MP 538 é um pneu radial multiusos, concebido especificamente para diversas aplicações e máquinas: motoniveladoras e pás carregadoras no inverno, bem como manipuladores telescópicos, veículos universais e varredoras na manutenção rodoviária.

Graças à lona de carcaça resistente com lonas de cima em aço, o MULTIMAX MP 538 permite o transporte de cargas pesadas mesmo a alta velocidade. Além disso, o design de piso único ajuda a manter excelente tração sobre gelo e neve.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Levantador telescópico • Veículo universal
Industrial: Motoniveladora • Carregadora

Version	STEEL BELTED
Type	TL
Tyre Size	405/70 R 20 MPT
LI/SS	152 G

Dimensions US Standard

Usa code	94069682
Section Width (inch)	16
Overall Diameter (inch)	42.4
Static Loaded Radius (inch)	19.1
Rolling Circumference (inch)	129.5
Rim Rec	W13

Load capacity (lbs)

mph / psi	87
55	7850
40	8500
25	9000

Printed on 28/04/2024 08:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..