

MULTIMAX MP 540 - Especificações técnicas



Description

O MULTIMAX MP 540 foi concebido pela BKT para todos os veículos multiusos. Graças à estrutura totalmente em aço, o MULTIMAX MP 540 permite transportar cargas pesadas em aplicações na estrada e fora dela. Além disso, o seu design com padrão de blocos proporciona uma estabilidade e durabilidade excepcionais

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Veiculo universal

Industrial: Veiculo universal

Version	STANDARD
Type	TL
Tyre Size	365/80 R 20 (14.5 R 20)
LI/SS	152 K

Dimensions International Standard

Overall Width (mm)	365
Overall Diameter (mm)	1086
Static Loaded Radius (mm)	495
Rolling Circumference (mm)	3308
Rim Rec	11
ECE	E11-54R-0020145

Load capacity (Kg)

km/h / bar	6.25
110	3550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07/12/2024 03:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..