

## MULTIMAX SR 261 - Especificações técnicas



### Description

O MULTIMAX SR 261 é um pneu radial integralmente em aço com lonas de cima em aço multicamadas, especialmente concebido para atrelados de plataforma baixa, atrelados agrícolas e guindastes móveis portuários, em aplicações de transporte e operações portuárias.

A carcaça forte e o composto especial do piso garantem uma maior vida útil. Graças ao piso com ranhuras, o MULTIMAX SR 261 permite uma tração superior em todas as aplicações.

Além disso, o design único do piso com 5 nervuras maximiza o contacto com o solo para um desgaste uniforme do piso.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Industrial: Reboque baixo • Guindaste móvel

Version	STANDARD
Type	TL
Tyre Size	285/70 R 19.5
LI/SS	150/148 J

## Dimensions International Standard

Overall Width (mm)	280
Overall Diameter (mm)	903
Static Loaded Radius (mm)	412
Rolling Circumference (mm)	2779
Rim Rec	8.25
Rim Alt	7.50 ; 9.00

## Load capacity (Kg)

	km/h / bar	9.00
100 Load Single		3350
100 Load Dual		3150

Printed on 19/04/2024 02:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..