

PAC MASTER PLUS - Especificações técnicas



Description

PAC MASTER PLUS é um pneu diagonal para compactadores, caracterizado por uma área de contacto mais larga, que oferece assim maior estabilidade. É realizado com um composto de borracha especial que fornece uma resistência elevada ao calor. PAC MASTER PLUS assegura um ciclo de vida prolongado do pneu.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Compactador

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 9.00 - 20 |

Dimensions International Standard

| | |
|-----------------------|-----------------|
| Ply Rating | 14 |
| Section Width (mm) | 270 |
| Overall Diameter (mm) | 1005 |
| Rim Rec | 7.0 |
| Rim Alt | 7.5 |
| ECE | E11-106R-005359 |

Load capacity (Kg)

| km/h / bar | 7.25 |
|------------|------|
| 10 | 4375 |
| 15 | 3445 |

Printed on 25/04/2024 18:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..