

## PAC MASTER - Especificações técnicas



### Description

PAC MASTER é um pneu diagonal para compactadores. Fornece uma estabilidade elevada e assegura um ciclo de vida prolongado. O pneu é realizado com um composto especial que fornece uma resistência especial ao calor.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Compactador

Version	STANDARD
Type	TL
Tyre Size	10.5/80 - 16

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	275
Overall Diameter (mm)	810
Static Loaded Radius (mm)	382
Rolling Circumference (mm)	2480
Rim Rec	8.0
ECE	E11-106R-004647

## Load capacity (Kg)

	km/h / bar	6.00
	10	2775
	15	2250

Printed on 25/04/2024 07:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..