

## PAC MASTER - Especificações técnicas



### Description

PAC MASTER é um pneu diagonal para compactadores. Fornece uma estabilidade elevada e assegura um ciclo de vida prolongado. O pneu é realizado com um composto especial que fornece uma resistência especial ao calor.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Compactador

Version	STANDARD
Type	TT
Tyre Size	9.00 - 20

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	275
Overall Diameter (mm)	1016
Static Loaded Radius (mm)	471
Rolling Circumference (mm)	3107
Rim Rec	7.0
Rim Alt	7.5
ECE	E11-106R-005360

## Load capacity (Kg)

km/h / bar	8.25
10	4750
15	3750

Printed on 25/04/2024 21:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..