

PL 801 - Especificações técnicas



Description

PL 801 foi concebido particularmente para aplicações com ancinhos recolhedores giratórios e viradores e juntadores, bem como para operações logísticas com empilhadores. O pneu proporciona uma estabilidade excelente junto com uma resistência elevada para todo o tipo de corte. PL 801 assegura um ciclo de vida prolongado do pneu.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Ceifeira • Ancinho rotativo • Empilhador
Industrial: Empilhador

Version	STANDARD
Type	TT
Tyre Size	21 X 8 - 9 (200/75 - 9)

Dimensions US Standard

Usa code	94006991
Ply Rating	14
Section Width (inch)	7.9
Overall Diameter (inch)	21.1
Rim Rec	6.00 E
Rim Alt	7.00 E
ECE	E11-106R-003643

Load capacity (lbs)

mph / psi	131
15 LOAD WHEEL	5590
15 STEER WHEEL	4300
5 OTHER VEHICLES	5590
15 OTHER VEHICLES	4300
STATIC SIDE LOADER	6490

Printed on 24/04/2024 09:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..