

## PL 801 - Especificações técnicas



### Description

PL 801 foi concebido particularmente para aplicações com ancinhos recolhedores giratórios e viradores e juntadores, bem como para operações logísticas com empilhadores. O pneu proporciona uma estabilidade excelente junto com uma resistência elevada para todo o tipo de corte. PL 801 assegura um ciclo de vida prolongado do pneu.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Ceifeira • Ancinho rotativo • Empilhador  
Industrial: Empilhador

Version	STANDARD
Type	TT
Tyre Size	6.00 - 9
LI/SS	A8 114

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	157
Overall Diameter (mm)	543
Rim Rec	4.00 E
ECE	E11-106R-003564

## Load capacity (Kg)

	km/h / bar	8.50
25 LOAD WHEEL		1715
25 STEER WHEEL		1320
10 OTHER VEHICLES		1715
25 OTHER VEHICLES		1320
STATIC SIDE LOADER		1995

Printed on 24/04/2024 10:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..