

## PL 801 - Especificações técnicas



### Description

PL 801 foi concebido particularmente para aplicações com ancinhos recolhedores giratórios e viradores e juntadores, bem como para operações logísticas com empilhadores. O pneu proporciona uma estabilidade excelente junto com uma resistência elevada para todo o tipo de corte. PL 801 assegura um ciclo de vida prolongado do pneu.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Ceifeira • Ancinho rotativo • Empilhador  
Industrial: Empilhador

Version	STANDARD
Type	TT
Tyre Size	7.00 - 15 (30 X 8 - 15)

## Dimensions US Standard

Usa code	94007363
Ply Rating	14
Section Width (inch)	8.1
Overall Diameter (inch)	30.5
Rim Rec	6.0
Rim Alt	5.50 BD ; 5.5

## Load capacity (lbs)

	mph / psi	145	150
15 LOAD WHEEL		6825	-
15 STEER WHEEL		5765	-
5 OTHER VEHICLES		5765	-
15 OTHER VEHICLES		4235	-
STATIC SIDE LOADER		-	9315

Printed on 24/04/2024 08:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..