

PL 801 - Dados técnicos



Description

PL 801 foi concebido particularmente para aplicações com ancinhos recolhedores giratórios e viradores e juntadores, bem como para operações logísticas com empilhadores. O pneu proporciona uma estabilidade excelente junto com uma resistência elevada para todo o tipo de corte. PL 801 assegura um ciclo de vida prolongado do pneu.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Ceifeira • Ancinho rotativo • Empilhador
Industrial: Empilhador

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
23 X 5 (23 X 5 (- 13))	STANDARD	94007028		6	3.75 P		6.1	25.2	TT	
18 X 7 - 8 (180/70 - 8)	STANDARD	94006953		14	4.33 R	5.00 F	6.8	18.5	TT	
18 X 7 - 8 (180/70 - 8)	STANDARD	94006977	121 A8	16	4.33 R	5.00 F	6.8	18.5	TT	E11-106R-003642
5.00 - 8	STANDARD	94007103		8	3.00 D	3.25 I	5.3	18.4	TT	E11-106R-003381
5.00 - 8	STANDARD	94032259		10	3.00 D	3.25 I	5.3	18.4	TT	
21 X 8 - 9 (200/75 - 9)	STANDARD	94027842		16	6.00 E	7.00 E	7.9	21.1	TT	
21 X 8 - 9 (200/75 - 9)	STANDARD	94006991		14	6.00 E	7.00 E	7.9	21.1	TT	E11-106R-003643
6.00 - 9	SPECIAL	94035052		10	4.00 E		6.2	21.4	TT	
6.00 - 9	STANDARD	94007127		10	4.00 E		6.2	21.4	TT	E11-106R-003564
6.00 - 9	STANDARD	94007158		12	4.00 E		6.2	21.4	TT	E11-106R-003565
6.50 - 10	STANDARD	94007165		10	5.00 F	5.50 F	7.3	23.4	TT	E11-106R-003566
7.00 - 12	STANDARD	94007196		12	5.00 S		7.4	27.2	TT	E11-106R-003567
7.00 - 12	STANDARD	94007219		14	5.00 S		7.4	27.2	TT	E11-106R-003398
250 - 15 (250/70 - 15)	STANDARD	94007059		16	7.50 BD	7.0 ; 7.5	9.3	29.3	TT	
250 - 15 (250/70 - 15)	STANDARD	94007066		20	7.50 BD	7.0 ; 7.5	9.3	29.3	TT	
300 - 15 (315/70 - 15)	STANDARD	94007080		18	8.00 BD	8.0	11.6	33.1	TT	E11-106R-007161
5.50 - 15	STANDARD	94030545		8	4.50 E DT	4.50 E SDC	6.2	26.4	TT	
7.00 - 15 (30 X 8 - 15)	STANDARD	94007363		14	6.0	5.50 BD ; 5.5	8.1	30.5	TT	
7.00 - 15 (29 X 8 - 15)	STANDARD	94007233		12	5.5	4.33 R ; 5.0	7.9	29.5	TT	
7.00 - 15 (30 X 8 - 15)	STANDARD	94007349		12	6.0	5.50 BD ; 5.5	8.1	30.5	TT	
7.50 - 15	STANDARD	94007370		12	6.0	6.00 S ; 6.5	8.7	30.9	TT	
7.50 - 15 (7.50 - 15 (32" OD))	STANDARD	94007325		14	6.0	6.00 S ; 6.5	8.7	32	TT	
7.50 - 15	STANDARD	94007387		14	6.0	6.00 S ; 6.5	8.7	30.9	TT	
8.15 - 15 (28 X 9 - 15)	STANDARD	94007257		12	7.0	7.00 BD	8.5	28.3	TT	
8.15 - 15 (28 X 9 - 15)	STANDARD	94007271		14	7.0	7.00 BD	8.5	28.3	TT	E11-106R-003631
8.25 - 15	STANDARD	94007295		12	6.5	6.0 ; 7.0	9.3	33.6	TT	
8.25 - 15	STANDARD	94007301		14	6.5	6.0 ; 7.0	9.3	33.6	TT	E11-106R-003402

Printed on 24/04/2024 03:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..