

## PORT KING CLASSIC - Especificações técnicas



### Description

PORT KING CLASSIC é o pneu de porto BKT de última geração, particularmente estudado para veículos para a movimentação de contentores. O pneu assegura a máxima eficiência operativa e estabilidade excepcional na modalidade de elevação. Graças à sua carcaça robusta em nylon, PORT KING CLASSIC distingue-se pela maior capacidade de carga, minimizando o risco de impactos como roturas, lacerações e perfurações. A nova mistura resistente ao desgaste foi desenvolvida para assegurar um ciclo de vida prolongado do produto, bem como um melhor retorno sobre o investimento.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Reach Stacker

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 - 25

## Dimensions US Standard

Usa code	94054480
Ply Rating	40
Overall Width (inch)	20.8
Overall Diameter (inch)	65.9
Static Loaded Radius (inch)	30.1
Rolling Circumference (inch)	195.1
Rim Rec	13.00 /2.5
Rim Alt	15.00/2.5
TRA Code	IND4

## Load capacity (lbs)

mph / psi	145
5	50625

Printed on 26/04/2024 10:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..