

## PORT KING PLUS - Especificações técnicas



### Description

PORT KING PLUS (IND-4) foi devidamente projetado para reach stacker nas aplicações de logística/transportes intermodais. O piso do pneu profundo com os grampos robustos, realizado com um composto de borracha especial, assegura um ciclo de vida prolongado do mesmo. É também disponível uma versão com um composto especialmente resistente às rachas nas estrias do piso do pneu "GCRC" (groove crack resistant compound).

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Reach Stacker

Version	GCRC
Type	TL
Tyre Size	18.00 - 25

## Dimensions International Standard

Ply Rating	40
Overall Width (mm)	528
Overall Diameter (mm)	1675
Static Loaded Radius (mm)	765
Rolling Circumference (mm)	4955
Rim Rec	13.00 /2.5
Rim Alt	15.00/2.5
TRA Code	IND4

## Load capacity (Kg)

km/h / bar	10.00
10	22950

Printed on 27/04/2024 18:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..