

PORT KING PLUS - Especificações técnicas



Description

PORT KING PLUS (IND-4) foi devidamente projetado para reach stacker nas aplicações de logística/transportes intermodais. O piso do pneu profundo com os grampos robustos, realizado com um composto de borracha especial, assegura um ciclo de vida prolongado do mesmo. É também disponível uma versão com um composto especialmente resistente às rachas nas estrias do piso do pneu "GCRC" (groove crack resistant compound).

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Reach Stacker

| | |
|-----------|------------|
| Version | GCRC |
| Type | TL |
| Tyre Size | 18.00 - 25 |

Dimensions International Standard

| | |
|----------------------------|------------|
| Ply Rating | 40 |
| Overall Width (mm) | 528 |
| Overall Diameter (mm) | 1675 |
| Static Loaded Radius (mm) | 765 |
| Rolling Circumference (mm) | 4955 |
| Rim Rec | 13.00 /2.5 |
| Rim Alt | 15.00/2.5 |
| TRA Code | IND4 |

Load capacity (Kg)

| | |
|------------|-------|
| km/h / bar | 10.00 |
| 10 | 22950 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 20/05/2025 15:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..