

## PORTMAX PM 90 - Especificações técnicas



### Description

PORTMAX PM 90 foi especificadamente projetado para empilhadeiras reach stacker em varias aplicações, tal como a manipulação industrial e as aciarias. O composto de borracha especial antiestático do piso do pneu assegura uma boa resistência ao calor e um ciclo de vida prolongado do pneu. PORTMAX PM 90 oferece uma resistência reduzida ao rolamento que melhora a poupança do combustível.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industrial: Reach Stacker

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 R 33
LI/SS	214 A5

## Dimensions US Standard

Usa code	94057184
Overall Width (inch)	19.1
Overall Diameter (inch)	72.6
Static Loaded Radius (inch)	33.7
Rolling Circumference (inch)	221.4
Rim Rec	13.00/2.50
Rim Alt	13.00/2.50 IF
Star Rating	***

## Load capacity (lbs)

mph / psi	145
15	46700

Printed on 24/04/2024 16:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..