

## PORTMAX PM 93 PLUS - Especificações técnicas



### Description

PORTMAX PM 93 PLUS foi especificadamente projetado para os empilhadores pórticos nas operações de movimentação de contentores em portos. O composto de borracha especial antiestático do piso do pneu assegura uma boa resistência ao calor e um ciclo de vida prolongado do pneu. PORTMAX PM 93 PLUS oferece uma resistência reduzida ao rolamento que melhora a poupança do combustível.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industrial: Pórtico automóvel

Version	INDUSTRIAL
Type	TL
Tyre Size	16.00 R 25
LI/SS	200 A5

## Dimensions US Standard

Usa code	94047680
Overall Width (inch)	16.7
Overall Diameter (inch)	59.6
Static Loaded Radius (inch)	27.5
Rolling Circumference (inch)	180.4
Rim Rec	11.25/2.0
Star Rating	**

## Load capacity (lbs)

mph / psi	145
15	30900

Printed on 04/03/2024 13:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..