

## POWER TRAX HD (FL) - Especificações técnicas



### Description

O POWER TRAX HD é um pneu premium de estrutura diagonal, especialmente desenhado para equipamentos de empilhadeira em aplicações industriais. O piso profundo, a parede lateral de grande espessura e o revestimento resistente garantem uma durabilidade excepcional, minimizando o risco de perfuração e danos acidentais. O pneu apresenta uma excelente resistência ao corte, ao choque e a rasgos, que o torna adequado para superfícies de betão duras e ásperas. O rebordo de proteção da jante especialmente desenhado garante a proteção contra furos e danos na roda, na área da flange da jante.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Empilhador

Version	STANDARD
Type	TT
Tyre Size	300 - 15 (315/70 - 15)

## Dimensions US Standard

Usa code	94007776
Ply Rating	20
Section Width (inch)	11.8
Overall Diameter (inch)	33.3
Rim Rec	8.00

## Load capacity (lbs)

mph / psi	131
15 LOAD WHEEL	14330
15 STEER WHEEL	11025
5 OTHER VEHICLES	14330
15 OTHER VEHICLES	11025
STATIC SIDE LOADER	16645

Printed on 20/04/2024 15:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..