

## POWER TRAX HD (FL) - Especificações técnicas



### Description

O POWER TRAX HD é um pneu premium de estrutura diagonal, especialmente desenhado para equipamentos de empilhadeira em aplicações industriais. O piso profundo, a parede lateral de grande espessura e o revestimento resistente garantem uma durabilidade excepcional, minimizando o risco de perfuração e danos acidentais. O pneu apresenta uma excelente resistência ao corte, ao choque e a rasgos, que o torna adequado para superfícies de betão duras e ásperas. O rebordo de proteção da jante especialmente desenhado garante a proteção contra furos e danos na roda, na área da flange da jante.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Empilhador

Version	STANDARD
Type	TT
Tyre Size	7.00 - 12

## Dimensions US Standard

Usa code	94032228
Ply Rating	16
Section Width (inch)	8.1
Overall Diameter (inch)	26.6
Rim Rec	5.00 S

## Load capacity (lbs)

	mph / psi	145
15 LOAD WHEEL		6415
15 STEER WHEEL		4940
5 OTHER VEHICLES		6415
15 OTHER VEHICLES		4940
STATIC SIDE LOADER		7450

Printed on 20/04/2024 08:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..