

POWER TRAX HD SMOOTH - Especificações técnicas



Description

POWER TRAX HD SMOOTH é um pneu de alta qualidade, especificadamente projetado para operações portuárias e em minas subterrâneas. A especial proteção do flanco e o piso do pneu sólido previnem danos derivados de cortes e furos, que representam riscos comuns nestes ambientes exigentes. Se for necessário movimentar cargas pesadas, Power Trax HD Smooth é o pneu ideal para as suas exigências.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Movimentador para contentores • Empilhador
OTR: Veículo para minas subterrâneas

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20

Dimensions US Standard

Usa code	94062997
Ply Rating	28
Section Width (inch)	12.6
Overall Diameter (inch)	45.3
Rim Rec	8.50
Rim Alt	9.0

Load capacity (lbs)

mph / psi	145
15 LOAD WHEEL	20920
15 STEER WHEEL	16095
5 OTHER VEHICLES	20920
15 OTHER VEHICLES	16095
STATIC SIDE LOADER	24305

Printed on 24/04/2024 08:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..