

POWER TRAX HD (SS) - Dados técnicos



Description

O POWER TRAX HD é um pneu premium especialmente desenhado para equipamentos em aplicações portuárias e de mineração subterrânea. O seu piso profundo, a parede lateral de grande espessura e o revestimento resistente garantem uma durabilidade excepcional, minimizando o risco de perfuração e danos acidentais. O pneu apresenta uma excelente resistência ao corte, ao choque e a rasgos, que o torna adequado para superfícies de betão duras e ásperas. O rebordo de proteção da jante especialmente desenhado garante a proteção contra furos e danos na roda, na área da flange da jante.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Minicarregadora

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10 - 16.5	IMPLEMENT	120 A8	10	8.25		268	790	361	2331	TL	E11-106R-003531
10 - 16.5	STANDARD		10	8.25		268	790	361	2331	TL	
12 - 16.5	STANDARD		10	9.75		324	865	391	2552	TL	
12 - 16.5	STANDARD		12	9.75		324	865	391	2552	TL	E11-106R-005557
12 - 16.5	STANDARD		14	9.75		324	865	391	2552	TL	E11-106R-005562

Printed on 23/04/2024 18:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..