

## POWER TRAX - Especificações técnicas



### Description

O POWER TRAX é um pneu premium especialmente concebido para trabalhos pesados com reboques portuários, manipuladores de contentores vazios e máquinas de mineração subterrâneas. O piso profundo e a lona de carcaça resistente proporcionam uma durabilidade excepcional, minimizando o risco de furos e danos acidentais. O POWER TRAX é o pneu ideal para operações duras e difíceis, graças ao composto único do piso que oferece excelente resistência a cortes e "chips".

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Movimentador para contentores vazios  
OTR: Veículo para minas subterrâneas

Version	STANDARD
Type	TL
Tyre Size	355/65 - 15
LI/SS	170 A5

## Dimensions US Standard

Usa code	94506330
Ply Rating	24
Section Width (inch)	13.2
Overall Diameter (inch)	32.7
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	99.6
Rim Rec	9.75

## Load capacity (lbs)

mph / psi	145
15 LOAD WHEEL	17200
15 STEER WHEEL	13225
5 OTHER VEHICLES	17200
15 OTHER VEHICLES	13225
STATIC SIDE LOADER	19975

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07/12/2024 22:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..