

POWERTRAILER SR 331 - Especificações técnicas



Description

O POWERTRAILER SR 331 é o novíssimo pneu radial integralmente em aço da BKT concebido especificamente para atrelados e camiões-cisterna em aplicações de transporte. Criado para utilização em estrada e no campo, o POWERTRAILER SR 331 distingue-se com as suas propriedades de boa flutuação no campo bem como com a excelente tração no asfalto ou noutras superfícies duras e melhoradas. A construção integralmente em aço traduz-se numa capacidade de carga elevada, extraordinária estabilidade da estrutura e duração prolongada do pneu. A nervura especial da parede lateral proporciona uma proteção excecional contra impactos e os efeitos da fricção no pneu, enquanto o talão hexagonal com reforço antifricção garante que o pneu se ajusta perfeitamente à jante. Adicionalmente, o padrão de piso multibloco garante uma resistência reduzida ao rolamento, pressão de contacto uniforme e suavidade de condução. Graças a todas estas características, o POWERTRAILER SR 331 é sinónimo de economia de combustível e conforto na estrada.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Cisterna móvel • Reboque

Version	IMPLEMENT
Type	TL
Tyre Size	560/60 R 22.5
LI/SS	169 D

Dimensions US Standard

Usa code	94075997
Overall Width (inch)	21.9
Overall Diameter (inch)	49
Static Loaded Radius (inch)	22.2
Rolling Circumference (inch)	148.6
Rim Rec	AG 16.00
Rim Alt	17.00 ; AG18.00
ECE	E11-106R-0010147

Load capacity (lbs)

mph/psi	46	52	58	65	73	80	87
5	14960	16340	17960	19100	20250	21640	23020
15	13130	14340	15760	16770	17780	18990	20210
25	11300	12350	13570	14430	15300	16350	17390
30	10050	10990	12070	12840	13610	14540	15480
40	8310	9080	9970	10610	11250	12020	12800
43	7560	8260	9070	9660	10240	10930	11640

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/02/2025 13:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..