

PRO RIB F2M - Especificações técnicas



Description

PRO RIB F2M é um pneu agrícola a ser utilizado com tratores 2WD/2RM nas operações para trabalhar o terreno. O pneu é especialmente apropriado para todas as operações que exigem um nível elevado de manuseamento.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Trator 2WD

Industrial: Reboque

Version	STANDARD
Type	TL
Tyre Size	14L - 16.1 SL
LI/SS	127 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	355
Overall Diameter (mm)	980
Static Loaded Radius (mm)	453
Rolling Circumference (mm)	2920
Rim Rec	W 11 C
ECE	E4-106R-002331
TRA Code	F2M

Load capacity (Kg)

km/h / bar	3.60
40	1750

Printed on 28/04/2024 02:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..