

## PRO RIB F2M - Especificações técnicas



### Description

PRO RIB F2M é um pneu agrícola a ser utilizado com tratores 2WD/2RM nas operações para trabalhar o terreno. O pneu é especialmente apropriado para todas as operações que exigem um nível elevado de manuseamento.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Trator 2WD

Industrial: Reboque

|           |              |
|-----------|--------------|
| Version   | STANDARD     |
| Type      | TL           |
| Tyre Size | 9.5L - 15 SL |
| LI/SS     | 102 A8       |

## Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Ply Rating                 | 8              |
| Section Width (mm)         | 240            |
| Overall Diameter (mm)      | 780            |
| Static Loaded Radius (mm)  | 364            |
| Rolling Circumference (mm) | 2325           |
| Rim Rec                    | 7.00           |
| Rim Alt                    | 8 LB           |
| ECE                        | E4-106R-002644 |
| TRA Code                   | F2M            |

## Load capacity (Kg)

| km/h / bar | 3.30 |
|------------|------|
| 40         | 850  |

Printed on 27/04/2024 19:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..