

## PUDDLE SPECIAL (B) - Especificações técnicas



### Description

PUDDLE SPECIAL é um pneu agrícola R-2 especialmente projetado para operações nos arrozais. O desenho super profundo do piso do pneu, para além da disposição especial das barras do pneu, assegura uma ótima adesão e uma excelente tração, mesmo em terreno molhado e macio. O largo elemento central proporciona uma melhor capacidade de adaptação para aplicações em estrada, para além de excelentes prestações operacionais. Por fim, PUDDLE SPECIAL apresenta ótimas propriedades de autolimpagem e durabilidade elevadas.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Pulverizador agrícola

Version	STANDARD
Type	TL
Tyre Size	120/90 - 26
LI/SS	90 A2

## Dimensions US Standard

Usa code	94059638
Ply Rating	6
Section Width (inch)	5
Overall Diameter (inch)	37
Static Loaded Radius (inch)	17.6
Rolling Circumference (inch)	112.1
Rim Rec	4 JA
ECE	E11-106R-005236

## Load capacity (lbs)

mph / psi	44
5	1320

Printed on 25/04/2024 17:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..