RIB 713 - Especificações técnicas

Description

RIB 713 é um pneu com cintos em aço para implementos agrícolas. Em resposta ao crescente conhecimento em questões de baixa compactação do solo na agricultura moderna, RIB 713 foi desenvolvido com a tecnologia IF. Por conseguinte, o pneu é capaz de suportar cargas mais pesadas a pressões de enchimento inferiores e fornece uma pegada mais larga com distribuição uniforme do peso. A estrutura cinturada em aço garante uma resistência extraordinária à perfuração e portanto uma maior proteção contra a penetração de hastes e consequentes danos, mesmo em presença de restolhos insidiosos. Além disso, a categoria velocidade "D" (65 km/h – 40 mph) permite deslocações rápidas na estrada. RIB 713 é o contributo BKT para maximizar a produtividade e a eficiência da sua empresa agrícola.

UM

International Standard

Construction

RADIAL

Machinery

Agricultura: Implementos agrícolas

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	IF 280/70 R 15
LI/SS	134 D

Dimensions International Standard

TKPH	1
Section Width (mm)	279
Overall Diameter (mm)	779
Static Loaded Radius (mm)	347
Rolling Circumference (mm)	2356
SRI (mm)	360
Rim Rec	W 8
ECE	E11-106R-005094
TRA Code	I1

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
From 10 to 65 km/h	775	885	1010	1120	1225	1335	1425	1570	1695	1800	1995	2120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/10/2024 04:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..