

RIB 774 (A) - Especificações técnicas



Description

RIB 774 (A) é um pneu de seção baixa para implementos agrícolas, que proporciona uma capacidade elevada de carga junto com um ciclo de vida prolongado. O pneu é ideal para aplicações com compressores de palha e reboques.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Enfardadeira de feno • Ceifeira • Reboque

| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 18 X 8.50 - 8 |
| LI/SS FREE ROLLING | 85 A8 |

Dimensions US Standard

| | |
|------------------------------|-------------------------------|
| Usa code | 94056910 |
| Ply Rating | 6 |
| Section Width (inch) | 8.9 |
| Overall Diameter (inch) | 18.1 |
| Static Loaded Radius (inch) | 8.5 |
| Rolling Circumference (inch) | 54.7 |
| Rim Rec | 7.00 I - 55 ; I - 70 ; I - 90 |
| ECE | E11-106R-004622 |

Load capacity (lbs)

| mph / psi | 44 |
|-----------|------|
| 5 FR | 1590 |
| 15 FR | 1360 |
| 20 FR | 1270 |
| 25 FR | 1140 |

Printed on 15/04/2024 10:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..