

## RIB 774 (A) - Especificações técnicas



### Description

RIB 774 (A) é um pneu de seção baixa para implementos agrícolas, que proporciona uma capacidade elevada de carga junto com um ciclo de vida prolongado. O pneu é ideal para aplicações com compressores de palha e reboques.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Enfardadeira de feno • Ceifeira • Reboque

Version	STANDARD
Type	TL
Tyre Size	200/60 - 14.5
LI/SS FREE ROLLING	113 A8

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	210
Overall Diameter (mm)	610
Static Loaded Radius (mm)	288
Rolling Circumference (mm)	1888
Rim Rec	AG 6.75
ECE	E11-106R-003608

## Load capacity (Kg)

	km/h / bar	7.00
	10 FR	1610
	25 FR	1370
	30 FR	1290
	40 FR	1150

Printed on 18/04/2024 09:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..