RIB 774 (B) - Especificações técnicas

Description

RIB 774 (B) é um pneu de seção baixa para implementos agrícolas, ideal para a agricultura moderna. O pneu é apropriado para aplicações em estrada e fora da estrada com implementos agrícolas e reboques. O pneu fornece uma capacidade elevada de carga e um ciclo de vida prolongado. O pneu é disponível em versão especial para as operações de serviço pesadas.

UM

International Standard

Construction

BIAS

Machinery

Agricultura: Implementos agrícolas • Reboque
Industrial: Reboque

Version	STANDARD
Type	TL
Tyre Size	15.0/55 - 17
LI/SS FREE ROLLING	141 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	391
Overall Diameter (mm)	850
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2490
Rim Rec	13.00
Rim Alt	13
ECE	E11-106R-004311

Load capacity (Kg)

km/h / bar	3.70
10 FR	3605
25 FR	3065
30 FR	2885
40 FR	2575

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/10/2024 11:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..