

## RIB 774 (B) - Especificações técnicas



### Description

RIB 774 (B) é um pneu de seção baixa para implementos agrícolas, ideal para a agricultura moderna. O pneu é apropriado para aplicações em estrada e fora da estrada com implementos agrícolas e reboques. O pneu fornece uma capacidade elevada de carga e um ciclo de vida prolongado. O pneu é disponível em versão especial para as operações de serviço pesadas.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Implementos agrícolas • Reboque  
Industrial: Reboque

Version	STANDARD
Type	TL
Tyre Size	15.0/55 - 17
LI/SS FREE ROLLING	141 A8

## Dimensions US Standard

Usa code	94010967
Ply Rating	14
Section Width (inch)	15.4
Overall Diameter (inch)	33.5
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	98
Rim Rec	13.00
Rim Alt	13
ECE	E11-106R-004311

## Load capacity (lbs)

mph / psi	54
5 FR	7950
15 FR	6760
20 FR	6360
25 FR	5680

Printed on 25/04/2024 00:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..