

RIB 774 (C) - Especificações técnicas



Description

RIB 774 (C) é um pneu de seção baixa com base estreita (narrow) para implementos agrícolas. É ideal para aplicações de recolha de palha e de transporte com compressores de palha e reboques. O pneu fornece uma capacidade elevada de carga e um ciclo de vida prolongado.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Enfardadeira de feno • Ceifeira • Reboque

Version	STANDARD
Type	TL
Tyre Size	215/75 - 17.5
LI/SS FREE ROLLING	139 A8

Dimensions International Standard

Ply Rating	16
Section Width (mm)	220
Overall Diameter (mm)	775
Static Loaded Radius (mm)	360
Rolling Circumference (mm)	2310
Rim Rec	6.75
ECE	E4-54R-0015341

Load capacity (Kg)

	km/h / bar	9.00
	10 FR	3710
	25 FR	3155
	30 FR	2970
	40 FR	2650

Printed on 13/04/2024 20:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..