

## RIB IMPLEMENT (A) - Especificações técnicas



### Description

RIB IMPLEMENT (A) foi projetado para reboques e implementos agrícolas nas aplicações de transporte e para trabalhar a terra. O pneu é ideal para as empresas agrícolas modernas e proporciona prestações excelentes, tanto na estrada como fora da estrada. RIB IMPLEMENT (A) é a escolha certa para todas as condições operacionais que exigem um nível elevado de manuseamento e manobras, bem como uma compactação do solo reduzida para conservar as culturas.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Agricultura: Implementos agrícolas • Reboque

Version	STANDARD
Type	TL
Tyre Size	10.0/80 - 12
LI/SS FREE ROLLING	110 A8

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	264
Overall Diameter (mm)	746
Static Loaded Radius (mm)	329
Rolling Circumference (mm)	2186
Rim Rec	9.00
Rim Alt	7.0
ECE	E11-106R-003533

## Load capacity (Kg)

km/h / bar	2.30
10 FR	1485
25 FR	1260
30 FR	1185
40 FR	1060

Printed on 23/04/2024 16:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..