

## RIDEMAX FL 690 - Especificações técnicas



### Description

RIDEMAX FL 690 é um pneu radial Flotation e de transporte idóneo para reboques, cisternas móveis e espalhadores. É um pneu principalmente destinado a ser utilizado 75% para aplicações na estrada. Para responder às exigências de cargas mais pesadas na agricultura moderna, a BKT desenhou este pneu com cintos em aço para o tornar forte e cargas muito pesadas, aumentando a produtividade do agricultor. A baixa resistência ao rolamento contribui para uma melhor economia de combustível.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Cisterna móvel • Reboque  
Industrial: Reboque

Version	STANDARD
Type	TL
Tyre Size	30.5L R 32
LI/SS	184 A8/181 B

## Dimensions US Standard

Usa code	94033836
Section Width (inch)	31.1
Overall Diameter (inch)	70.9
Static Loaded Radius (inch)	31.7
Rolling Circumference (inch)	213.8
Rim Rec	DH 27 B
Rim Alt	DW 27 B
ECE	E11-106R-002986

## Load capacity (lbs)

mph / psi	12	15	20	23	29	35	41	44
30	8370	9640	11640	12550	14370	16000	17460	18190
25	9630	11090	13390	14440	16530	18420	20090	20920
20	10880	12530	15130	16320	18680	20810	22710	23640
15	11470	13220	15960	17210	19700	21930	23930	24920
5	13320	15330	18520	19960	22850	25460	27780	28920

Printed on 18/04/2024 22:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..