

RIDEMAX FL 690 - Especificações técnicas



Description

RIDEMAX FL 690 é um pneu radial Flotation e de transporte idóneo para reboques, cisternas móveis e espalhadores. É um pneu principalmente destinado a ser utilizado 75% para aplicações na estrada. Para responder às exigências de cargas mais pesadas na agricultura moderna, a BKT desenhou este pneu com cintos em aço para o tornar forte e cargas muito pesadas, aumentando a produtividade do agricultor. A baixa resistência ao rolamento contribui para uma melhor economia de combustível.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Cisterna móvel • Reboque
Industrial: Reboque

Version	STANDARD
Type	TL
Tyre Size	800/60 R 32
LI/SS	185D

Dimensions International Standard

Section Width (mm)	800
Overall Diameter (mm)	1800
Static Loaded Radius (mm)	817
Rolling Circumference (mm)	5454
SRI (mm)	850
Rim Rec	DH 27 B
Rim Alt	DW 27 B
ECE	E11-106R-006480

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	2695	3455	4295	4885	5645	6400	6990	7665	8420
65	2960	3795	4720	5365	6200	7030	7680	8420	9250
50	3585	4590	5710	6495	7505	8510	9295	10190	11195
40	4030	5160	6420	7300	8430	9565	10445	11450	12580
30	4475	5730	7125	8105	9360	10620	11600	12715	13970
25	4680	5995	7455	8480	9795	11110	12135	13300	14615
10	5330	6830	8495	9660	11160	12655	13820	15155	16650

Printed on 19/04/2024 01:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..