

RIDEMAX FL 693 M - Especificações técnicas



Description

RIDEMAX FL 693 M é o pneu ideal para quem tem de percorrer frequentemente troços rodoviários com reboques/cisternas móveis. Realizado para uma utilização de 75% na estrada, RIDEMAX FL 6936 M mostra prestações excelentes na estrada, dando a prioridade ao conforto e às propriedades de auto limpeza. O índice de velocidade classe D/E da gama é sinónimo de velocidades mais elevadas em percursos rodoviários com enorme poupança de tempo. A baixa resistência ao rolamento contribui para um consumo menor de combustível, enquanto o talão reforçado e os cintos de aço asseguram maior durabilidade.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Cisterna móvel • Reboque

| | |
|-----------|---------------|
| Version | HD |
| Type | TL |
| Tyre Size | 710/50 R 26.5 |
| LI/SS | 179 D |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 727 |
| Overall Diameter (mm) | 1383 |
| Static Loaded Radius (mm) | 606 |
| Rolling Circumference (mm) | 4217 |
| SRI (mm) | 650 |
| Rim Rec | AG 24.00 |
| Rim Alt | AG 20.00 |
| ECE | E11-106R-006008 |

Load capacity (Kg)

| km/h / bar | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 5.0 | 6.0 |
|------------|------|------|------|------|------|------|------|------|-------|-------|-------|
| 70 | 1765 | 2260 | 2825 | 3175 | 3670 | 4165 | 4590 | 5010 | 5505 | 6210 | 7055 |
| 65 | 1940 | 2480 | 3100 | 3490 | 4030 | 4575 | 5040 | 5505 | 6045 | 6820 | 7750 |
| 50 | 2345 | 3005 | 3755 | 4225 | 4880 | 5535 | 6100 | 6660 | 7320 | 8255 | 9380 |
| 40 | 2635 | 3375 | 4220 | 4745 | 5485 | 6220 | 6855 | 7485 | 8225 | 9280 | 10540 |
| 30 | 2930 | 3750 | 4685 | 5270 | 6090 | 6910 | 7610 | 8315 | 9130 | 10305 | 11705 |
| 25 | 3065 | 3920 | 4900 | 5515 | 6370 | 7225 | 7960 | 8695 | 9555 | 10780 | 12245 |
| 10 | 3490 | 4465 | 5580 | 6280 | 7255 | 8235 | 9070 | 9905 | 10885 | 12280 | 13950 |

Printed on 29/04/2024 02:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..