

## RIDEMAX IT 696 - Dados técnicos



### Description

RIDEMAX IT 696 é dotado de um único desenho do piso do pneu e uma pegada larga que fornece uma adesão excelente para aplicações na estrada, também no inverno. O pneu é muito apropriado para aplicações de transporte, nas obras de municipalidade e na manutenção graças às características da alta velocidade e a carcaça robusta. O desenho do piso do pneu foi concebido particularmente para as operações de serviço pesadas e para uma baixa resistência ao rolamento que se traduz numa economia de combustível e ótima estabilidade.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Trator

| SIZE                               | Version  | LI/SS        | RIM REC            | RIM ALT                 | SW  | OD   | SLR | RC   | SRI | Type | TKPH | ECE             |
|------------------------------------|----------|--------------|--------------------|-------------------------|-----|------|-----|------|-----|------|------|-----------------|
| <b>240/70 R 16 IND</b>             | STANDARD | 107A8/107B   | W8                 | W9                      | 244 | 742  | 343 | 2226 | 350 | TL   |      | E11-106R-006942 |
| <b>340/80 R 18 IND</b>             | STANDARD | 143 A8/138 D | 11 ; 11 SDC ; W 11 | W 10 ; 12 ; 12 SDC      | 343 | 1001 | 458 | 2980 | 475 | TL   |      | E11-106R-002987 |
| <b>360/80 R 20 IND</b>             | STANDARD | 143D/147A8   | 11                 | W 10 ; W 11 ; 12 ; W 12 | 357 | 1084 | 488 | 3235 | 525 | TL   |      | E11-106R-007845 |
| <b>300/80 R 24 IND (11.2 R 24)</b> | STANDARD | 133 A8/128 D | DW 10              |                         | 295 | 1090 | 501 | 3296 | 525 | TL   |      | E4-106R-002292  |
| <b>340/80 R 24 IND (12.4 R 24)</b> | STANDARD | 140 A8/135 D | DW 11              | W 10 ; W 12 ; DW 10     | 343 | 1154 | 521 | 3444 | 550 | TL   |      | E4-106R-002293  |
| <b>360/80 R 24 IND (13.6 R 24)</b> | STANDARD | 143 A8/138 D | DW 11              | W 12 ; W 10             | 343 | 1186 | 537 | 3556 | 575 | TL   |      | E11-106R-004753 |
| <b>400/80 R 24 IND (14.9 R 24)</b> | STANDARD | 149 A8/144 D | DW 13              | W 12 ; W 14 L           | 404 | 1250 | 558 | 3760 | 600 | TL   |      | E4-106R-002400  |
| <b>420/65 R 24 IND</b>             | STANDARD | 146 D/151 A8 | DW 13 L ; W13      | DW 15 L ; DW 14 L       | 418 | 1158 | 530 | 3483 | 550 | TL   | 1    | E11-106R-005952 |
| <b>440/80 R 24 IND (16.9 R 24)</b> | STANDARD | 154 A8/149 D | DW 14 L            | DW 15 L ; DW 13         | 441 | 1314 | 590 | 3939 | 625 | TL   |      | E11-106R-004760 |
| <b>460/65 R 24 IND</b>             | STANDARD | 151 D/156 A8 | DW 14 L            | DW 15 L ; DW 13         | 455 | 1214 | 549 | 3644 | 600 | TL   | 1    |                 |
| <b>500/70 R 24 IND</b>             | STANDARD | 164A8/159D   | DW 16 L            | DW 15 L ; DW 18 L       | 503 | 1310 | 602 | 3954 | 625 | TL   |      | E11-106R-007547 |
| <b>500/70 R 24 IND</b>             | STANDARD | 157 A8/152 D | DW 16 L            | DW 15 L ; DW 18 L       | 503 | 1310 | 602 | 3954 | 625 | TL   |      | E11-106R-007051 |
| <b>400/80 R 28 IND (14.9 R 28)</b> | STANDARD | 151 A8/146 D | W 13               | W 12 ; W 14 L           | 404 | 1352 | 615 | 4048 | 650 | TL   |      | E4-106R-002401  |
| <b>440/80 R 28 IND (16.9 R 28)</b> | STANDARD | 156 A8/151 D | W 14 L             | W 15 L                  | 441 | 1415 | 634 | 4288 | 675 | TL   |      | E4-106R-002299  |
| <b>440/80 R 30 IND (16.9 R 30)</b> | STANDARD | 157 A8/153 D | W 14 L             | W 15 L                  | 441 | 1466 | 668 | 4456 | 700 | TL   |      | E4-106R-002297  |
| <b>480/80 R 30 IND (18.4 R 30)</b> | STANDARD | 162 A8/157 D | W 15 L             | W 16 L                  | 479 | 1530 | 673 | 4558 | 725 | TL   |      | E4-106R-002298  |
| <b>440/80 R 34 IND (16.9 R 34)</b> | STANDARD | 159 A8/155 D | DW 14 L            | DW 15 L ; DW 16 L       | 441 | 1567 | 704 | 4775 | 750 | TL   |      | E4-106R-002295  |
| <b>480/80 R 34 IND (18.4 R 34)</b> | STANDARD | 164 A8/159 D | W 15 L             | W 16 L                  | 479 | 1632 | 728 | 4894 | 775 | TL   |      | E4-106R-002296  |
| <b>480/80 R 38 IND (18.4 R 38)</b> | STANDARD | 166 A8/161 D | W 15 L             | W 16 L                  | 479 | 1733 | 780 | 5213 | 825 | TL   |      | E11-106R-004075 |
| <b>540/80 R 38 IND</b>             | STANDARD | 172 A8/167 D | W 18 L             | W 16 L                  | 550 | 1829 | 833 | 5537 | 875 | TL   |      | E11-106R-004077 |
| <b>540/80 R 42 IND</b>             | STANDARD | 168 D/173 A8 | W 18 L             | W 16 L                  | 560 | 1931 | 879 | 5875 | 925 | TL   |      | E11-106R-005714 |

Printed on 02/03/2024 20:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The

user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..