RIDEMAX IT 697 (M+S) - Especificações técnicas

Description

RIDEMAX IT 697 M+S é a resposta perfeita às exigências das empresas modernas sob contrato no segmento da agricultura para as operações no período invernal. É perfeito para aplicações de transporte e de municipalidade. Este pneu invernal para tratores garante uma aderência perfeita em todas as operações em terrenos cobertos de gelo e de neve, sem nenhuma necessidade de utilizar correntes de neve. Graças às ranhuras do piso do pneu e ao composto especial, o trator conduz-se com grande estabilidade mesmo as altas velocidades. O desenho do piso do pneu foi concebido particularmente para as operações de serviço pesadas e assegura uma baixa resistência ao rolamento além de ótima estabilidade.

UM

US Standard

Construction

RADIAL

Machinery

Agricultura: Trator

Version	STANDARD
Type	TL
Tyre Size	600/70 R 30 IND
LI/SS	166 D/171 A8

Dimensions US Standard

Usa code	94058037
TMPH	1
Section Width (inch)	23.6
Overall Diameter (inch)	63
Static Loaded Radius (inch)	27.1
Rolling Circumference (inch)	189.8
Rim Rec	DW 18 L
Rim Alt	DW 20 B
ECE	E11-106R-005177

Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	5490	6780	7950	9230	10390	11680
30	5930	7320	8590	9980	11230	12620
25	6370	7860	9210	10710	12070	13560
20	6590	8130	9530	11080	12480	14020

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/10/2024 08:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..