RIDEMAX IT 697 (M+S) - Dados técnicos

Description

RIDEMAX IT 697 M+S é a resposta perfeita às exigências das empresas modernas sob contrato no segmento da agricultura para as operações no período invernal. É perfeito para aplicações de transporte e de municipalidade. Este pneu invernal para tratores garante uma aderência perfeita em todas as operações em terrenos cobertos de gelo e de neve, sem nenhuma necessidade de utilizar correntes de neve. Graças às ranhuras do piso do pneu e ao composto especial, o trator conduz-se com grande estabilidade mesmo as altas velocidades. O desenho do piso do pneu foi concebido particularmente para as operações de serviço pesadas e assegura uma baixa resistência ao rolamento além de ótima estabilidade.

UM

International Standard

Construction

RADIAL

Machinery

Agricultura: Trator

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	TKPH	ECE
460/70 R 24 IND	STANDARD	157A8/152D	DW 15 L	DW14 L; DW 16L	465	1254	571	3772	600	TL		E11-106R-006840
540/70R24 IND	STANDARD	170D/175A8	DW 16 L	DW18 L	535	1370	625	4181	650	TL		E11-106R-007933
480/65 R 28 IND	STANDARD	149 D/154 A8	DW 15 L	DW 14 L ; DW 16 L	480	1335	615	4088	650	TL		E11-106R-006159
540/65 R28 IND	STANDARD	155 D/160 A8	W 16 L	W 18	530	1413	642	4276	675	TL		E11-106R-004076
600/65 R 28 IND	STANDARD	165 A8/160 D	W 18 L	DW 20 B	591	1491	684	4509	700	TL		E11-106R-006760
540/65 R 30 IND	STANDARD	156 D/161 A8	W 16 L	W 18	530	1464	672	4445	700	TL		E11-106R-003015
600/70 R 30 IND	STANDARD	166 D/171 A8	DW 18 L	DW 20 B	600	1600	688	4820	750	TL	1	E11-106R-005177
600/65 R 38 IND	STANDARD	166 D/170 A8	DW 18 L	DW 20 B	590	1745	795	5315	825	TL		E11-106R-005855
650/65 R 38 IND	STANDARD	170 D/175 A8	DW 20 B	DW 18 L	645	1811	823	5514	875	TL	1	E11-106R-004078
650/85 R 38 IND	STANDARD	178 D/ 183 A8	DW 23 B	DW 20 B ; DW 21 B	709	2071	974	6280	975	TL		E11-106R-006761
710/70 R 38 IND	STANDARD	177D / 182A8	DW 23 B	DW 25 B	716	1959	900	5950	925	TL		E11-106R-006762
650/65 R 42 IND	STANDARD	171 D/176 A8	DW 20 B	DW 18 L	645	1920	880	5869	925	TL		E4-106R-002659
710/70 R 42 IND	STANDARD	180 D/185 A8	DW23 B		716	2068	926	6264	975	TL	1	'E11-106R-005178

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/10/2024 09:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..