

RM 2002 - Especificações técnicas



Description

RM 2002 é um pneu apropriado para as operações de transporte com reboques e camiões ligeiros, tanto na estrada como fora da estrada. O pneu assegura uma longa duração e performances elevadas durante todo o ciclo de vida do produto. A sua versão "industrial" é ideal para guindastes móveis "pick & carry".

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Reboque

Industrial: Guindaste móvel

Version	STANDARD
Type	TT
Tyre Size	11.00 - 20

Dimensions International Standard

Ply Rating	18
Section Width (mm)	302
Overall Diameter (mm)	1101
Rim Rec	8.0
Rim Alt	7.5 ; 8.5

Load capacity (Kg)

	km/h / bar	8.25	7.60
100 LS		3350	-
100 LD		-	3000

Printed on 26/04/2024 20:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..