# RM 500 - Dados técnicos

## Description

RM 500 é um pneu radial com cintos em aço, apropriado para aplicações de colheita com implementos agrícolas. O pneu é dotado de uma carcaça robusta e um desenho especial do piso do pneu que proporcionam uma capacidade de carga elevada e uma resistência excelente aos cortes e lacerações. Graças à sua ampla área de contacto, RM 500 assegura uma ótima distribuição da pressão no terreno e uma compactação reduzida do solo, além de uma tração excelente.

## UM

US Standard

## Construction

RADIAL

## Machinery

Agricultura: Ceifeira

| SIZE | Version | USACode | LI/SS | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **500/70 R 24** | STEEL BELTED | 94062430 | 167 A8 / 155 A8 | 155 A8 | 167 A8 | W 16 L | W 15 L | 19.8 | 51.6 | 22.5 | 153.8 | TL | E11-106R-005989 |
| **500/85 R 24** | STEEL BELTED | 94061570 | 182 A8 / 170 A8 | 170 A8 | 182 A8 | W 16 L | W 15 L | 20.5 | 57.5 | 24.5 | 172.5 | TL | E11-106R-005991 |
| **500/80 R 28** | STEEL BELTED | 94063697 | 176 A8 / 164 A8 | 164 A8 | 176 A8 | W 16 L | W 15 L | 19.8 | 58.9 | 25 | 171.5 | TL | E11-106R-005990 |
| **600/65 R 28** | STEEL BELTED | 94070961 | 177A8/165A8 | 165 A8 | 177 A8 | W 18 L | W 20 L | 23.2 | 58.5 | 25.2 | 170.9 | TL | E11-106R-007699 |
| **600/65 R 28** | STEEL BELTED | 94063666 | 168 A8 / 156 A8 | 156 A8 | 168 A8 | W 18 L | W 20 L | 23.2 | 58.5 | 25.2 | 170.9 | TL | E11-106R-005993 |
| **500/85 R 30** | STEEL BELTED | 94065097 | 176A8/164A8 | 164 A8 | 176 A8 | W 16 L | W 15 L | 21.1 | 63.4 | 26.5 | 186.8 | TL | E11-106R-006398 |

Printed on 26/04/2024 21:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..