

ROCK GRIP (T) - Especificações técnicas



Description

ROCK GRIP (E-4) é ideal para dumper com caixa basculante nas aplicações para pedreiras e para transportes breves nas minas, suportando cargas pesadas. O composto de borracha especial do piso do pneu reduz no mínimo cortes e furos, mesmo em terrenos mais difíceis. ROCK GRIP (E-4) proporciona uma tração excepcional junto com um longo ciclo de vida.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Camião basculante • Dumper Rígido

Version	STANDARD
Type	TT
Tyre Size	12.00 - 24

Dimensions International Standard

Ply Rating	20
Overall Width (mm)	315
Overall Diameter (mm)	1265
Static Loaded Radius (mm)	595
Rolling Circumference (mm)	3755
Rim Rec	8.5
Rim Alt	8.0

Load capacity (Kg)

km/h / bar	7.90
80 LS/LD	3875

Printed on 15/08/2024 00:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..