

## RT 747 AGRO INDUSTRIAL - Especificações técnicas



### Description

RT 747 AGRO INDUSTRIAL é um pneu radial agroindustrial apropriado para retroescavadoras, pás compactas e telescópicas. Os blocos extra largos asseguram uma tração excelente e uma estabilidade extraordinária nas operações de levantamento. Foi projetado com um composto particularmente resistente aos cortes e lacerações para transportar cargas pesadas. RT 747 AGRO INDUSTRIAL é a resposta certa para todas as operações agrícolas que, geralmente, exigem uma versatilidade excepcional.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Carregadora compacta • Levantador telescópico

Industrial: Carregadora compacta • Levantador telescópico

Version	STANDARD
Type	TL
Tyre Size	11L R 16
LI/SS	122 A8/B

## Dimensions US Standard

Usa code	94062737
Section Width (inch)	11.4
Overall Diameter (inch)	33.5
Rim Rec	W 8
Rim Alt	W 10 L
ECE	E11-106R-005769

## Load capacity (lbs)

mph / psi	17	23	29	32	35	38
5	2790	3370	3950	4230	4530	4850
15	2070	2570	3050	3310	3550	---
25	1940	2390	2850	3080	3310	---

Printed on 28/04/2024 00:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..