

RT 857 - Especificações técnicas



Description

RT 857 é um pneu apropriado para aplicações para o trabalho do terreno. A carcaça robusta garante uma ótima durabilidade e excelente tração. O composto de borracha do piso do pneu é caracterizado por uma resistência elevada a todos os tipos de corte e restolho.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Trator

| | |
|-----------|----------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 320/85 R 24 (12.4 R 24) |
| LI/SS | 122 A8/B |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 329 |
| Overall Diameter (mm) | 1154 |
| Static Loaded Radius (mm) | 528 |
| Rolling Circumference (mm) | 3449 |
| SRI (mm) | 550 |
| Rim Rec | W 11 |
| Rim Alt | W 10 ; W 9 |
| ECE | E11-106R-002976 |
| TRA Code | R1 |

Load capacity (Kg)

| km/h / bar | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 50 | 825 | 960 | 1095 | 1230 | 1365 | 1500 |
| 40 | 825 | 960 | 1095 | 1230 | 1365 | 1500 |
| 30 | 885 | 1030 | 1175 | 1320 | 1465 | 1605 |
| 10 LT | 1110 | 1290 | 1470 | 1650 | 1830 | 2010 |
| 10 HT | 885 | 1030 | 1175 | 1320 | 1465 | 1605 |

Printed on 27/04/2024 05:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..