

## RT 857 - Especificações técnicas



### Description

RT 857 é um pneu apropriado para aplicações para o trabalho do terreno. A carcaça robusta garante uma ótima durabilidade e excelente tração. O composto de borracha do piso do pneu é caracterizado por uma resistência elevada a todos os tipos de corte e restolho.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Trator

Version	STANDARD
Type	TL
Tyre Size	380/85 R 24 (14.9 R 24)
LI/SS	131 A8/B

## Dimensions International Standard

Section Width (mm)	380
Overall Diameter (mm)	1256
Static Loaded Radius (mm)	566
Rolling Circumference (mm)	3783
SRI (mm)	600
Rim Rec	W 12
Rim Alt	W 13 ; W 11
ECE	E11-106R-002977
TRA Code	R1

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1075	1250	1425	1600	1775	1950
40	1075	1250	1425	1600	1775	1950
30	1150	1340	1530	1715	1905	2090
10 LT	1440	1675	1910	2145	2380	2615
10 HT	1150	1340	1530	1715	1905	2090

Printed on 27/04/2024 09:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..