

RT 857 - Especificações técnicas



Description

RT 857 é um pneu apropriado para aplicações para o trabalho do terreno. A carcaça robusta garante uma ótima durabilidade e excelente tração. O composto de borracha do piso do pneu é caracterizado por uma resistência elevada a todos os tipos de corte e restolho.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Trator

Version	STANDARD
Type	TL
Tyre Size	380/85 R 28 (14.9 R 28)
LI/SS	133 A8/B

Dimensions US Standard

Usa code	94042241
Section Width (inch)	15.4
Overall Diameter (inch)	53.4
Static Loaded Radius (inch)	24.3
Rolling Circumference (inch)	162.5
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E4-106R-000769
TRA Code	R1

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2500	2910	3320	3730	4130	4540
25	2500	2910	3320	3730	4130	4540
20	2680	3120	3550	3990	4430	4860
5 LT	3360	3900	4450	5000	5560	6100
5 HT	2680	3120	3550	3990	4430	4860

Printed on 27/04/2024 07:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..