

RT 857 - Especificações técnicas



Description

RT 857 é um pneu apropriado para aplicações para o trabalho do terreno. A carcaça robusta garante uma ótima durabilidade e excelente tração. O composto de borracha do piso do pneu é caracterizado por uma resistência elevada a todos os tipos de corte e restolho.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Trator

Version	STANDARD
Type	TL
Tyre Size	420/85 R 26 (16.9 R 26)
LI/SS	138 A8/B

Dimensions International Standard

Section Width (mm)	438
Overall Diameter (mm)	1374
Static Loaded Radius (mm)	616
Rolling Circumference (mm)	4115
SRI (mm)	650
Rim Rec	DW 15 L
Rim Alt	W 14 L ; W 15 L ; W 16 L ; DW 16 L
ECE	E11-106R-003471
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1300	1515	1725	1940	2150	2360
40	1300	1515	1725	1940	2150	2360
30	1395	1620	1850	2075	2305	2530
10 LT	1745	2030	2315	2600	2885	3165
10 HT	1395	1620	1850	2075	2305	2530

Printed on 27/04/2024 04:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..